



2015 DOT ROAD RACE TECHNICAL DATA*

LINE	POS	SIZE	COMPOUND(S)	>>> DURABILITY >>>	SKU	REC. RIM	RIM RANGE	WIDTH†	DIA†	INFLATION PRESSURE (PSI)	
						(Inches)	(MM)	COLD	HOT		
Unbeaten 02	F	110/70R17 (54W)			32UB69	3.0	2.75-3.5	110	589	30	33
	R	150/60R17 (66W)			32UB50	4.0	3.5-4.5	151	620	28	33
Alpha 13	F	110/70R17 (54H)			13AA01	3.0	2.75-3.5	107	589	30	33
	R	150/60R17 (66H)			13AA02	4.0	3.5-4.0	149	619	28	33
D211 GPA	F	120/70ZR17 (58W)	7455		310275	3.5	3.5-3.75	122	605	30-32	34-36
			8477		300275						
	R	160/60ZR17 (69W)	7455		320251	4.5	4.5-5.0	167	633	28	32
	R	190/55ZR17 (75W)	7455		310235	5.5	5.5-6.0	189	647	18-22	22-25
			8477		300235						
	R	190/60ZR17 (78W)	2662		300266	5.5	5.5-6.0	190	657	18-22	22-25
7455				330266							
8477				320266							
D212 GP	F	120/70ZR17 (58W)	Pro4		32ZL75	3.5	3.5-3.75	119	602	30-32	34-36
			9854		32XJ75						
	R	190/55ZR17 (75W)	9948		32CY65	5.5	5.5-6.0	190	649	21	23
			9056		32CZ65						
GPA-Pro	F	120/70ZR17 (58W)	7455		430004	3.5	3.5-3.75	122	605	30-32	34-36
			8477		430005						
	R	190/60ZR17 (78W)	2662		430001	5.5	5.5-6.0	190	657	18-22	22-25
			7455		430002						
			8477		430003						

Dunlop recommends that tire warmers be set at 70°-80°C for 45 minutes to 1 hour (maximum); tire performance degradation may occur if tires are subjected to repeated tire warming cycles, and/or temperatures/times in excess of these.

(*) Excluding Daytona
 (†) Measured on recommended rim



2015 NON-DOT ROAD RACE TECHNICAL DATA*

LINE	POS	SIZE	COMPOUND(S)	>>> DURABILITY >>>	SKU	REC. RIM	RIM RANGE	WIDTH†	DIA†	INFLATION PRESSURE (PSI)	
						(Inches)	(Inches)	(MM)	(MM)	COLD	HOT
KR448	F	120/70R17	7455		351485	3.5	3.5-3.75	117	608	30-32	34-36
			8477		351585						
KR449	R	165/55R17	7455		301449	5.0	4.5-5.25	158	632	26-28	30-32
	R	190/55R17	8477		301465	5.5	5.5-6.0	189	648	19-22	22-25
KR451	R	200/55R17	2662		351545	6.0	5.5-6.25	196	656	19-22	22-25
			7455		331545						
			8477		341545						
KR189 (WET)	F	110/70R17	WA		18KR01	3.0	2.75-3.5	117	588	29	NA
		120/70R17	WA		32FR75	3.5	3.5-3.75	120	600	33-36	NA
KR393 (WET)	R	140/65R17	WA		38KR02	4.0	3.0-4.0	141	620	29	NA
		190/55R17	414		33CQ65	6.0	5.5-6.25	190	649	33-36	NA

Dunlop recommends that tire warmers be set at 70°-80°C for 45 minutes to 1 hour (maximum); tire performance degradation may occur if tires are subjected to repeated tire warming cycles, and/or temperatures/times in excess of these. Dunlop does not recommend the use of tire warmers on rain tires.

(*) Excluding Daytona
 (†) Measured on recommended rim